SINGLE DOUBLE LEG WEBBING LANYARD PART CODE: WL01

PRODUCT INFORMATION >

2 Metre Webbing Lanyard WLO1 - Single Leg Webbing Lanyard + Hardware (Refer to Single Leg Lanyard Hardware Page).

PRODUCT FEATURES >

- An exclusive Extended Length Energy Absorber (ELEA) designed to protect a worker of up to 150kg, including tools and equipment.
- · Drop forged lanyard hardware.
- Stitching patterns are sewn by computer controlled bar tacking machinery for precision using UV resistant high tenacity polyester yarn with 100 newton (10kg) breaking strength.
- Unique THETA stitch pattern has over 313 stitches resulting in a seam that matches the lanyard's webbing strength, ensuring no weak point in the lanyard assembly.

PRODUCT DETAILS >

- AUS/NZ designed and engineered.
- High Tenacity webbing 28kN, 185% in excess of AS/NZS 1891.5:2020 requirements.
- · Contrast stitch thread colour for easy inspection.
- Standard LINQ shock absorber is rated for wearer of up to 150kg, including tooling and equipment.
- Drop forged D Transition point doubles as a spare leg stowage point.
- Custom lengths available on request, for example: 1.0m, 1.2m, 1.5m, 1.8m
- Webbing Material: Polyester; 45mm; UV Resilient; Solvent Resistant.
- Fall Arrest Hardware: Drop Forged corrosion resistant electrophoresis; high strength alloy steel.
- Stitch Pattern: THETA Pattern combines 313 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast.
- Web Tenacity: Min 30kN Max 33kN.

STANDARDS >







Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice. If in doubt please contact the LINQ helpline.

SINGLE LEG LANYARD HARDWARE

FOR COMPLETE CODE ADD LANYARD & HARDWARE CODE TOGETHER EG. SINGLE LEG WEBBING LANYARD WITH 2 X TRIPLE ACTION KARABINERS = WL01 + KTKT





Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice. If in doubt please contact the LINQ helpline.