

FLAT SLING

PART CODE: **SF(CAPACITY)(LENGTH)**



PRODUCT DESCRIPTION >

High tenacity, UV resistant, double ply Flat Sling.

PRODUCT FEATURES >

- Material: 100% High tenacity, UV resistant polyester for extreme UV conditions.
- Double ply flat slings.
- Working load designated by international protocol for load rating colours.
- All slings have capacity stripes woven into the sling material.
- Colour coded as per international protocol

PRODUCT DETAILS >

- **Capacity:** 1T – 5T (up to 20T available on request).
- **Safety Factor:** 8:1.

STANDARDS >

AS1353.1



ISO 9001
ISO 14001



COLOUR CODE GUIDE >

	1T				2T				3T				4T				5T		
	P.NO.	CAP.	LEN.		P.NO.	CAP.	LEN.		P.NO.	CAP.	LEN.		P.NO.	CAP.	LEN.		P.NO.	CAP.	LEN.
	SF01005	1T	0.5M		SF02005	2T	0.5M		SF03005	3T	0.5M		SF04005	4T	0.5M		SF05010	5T	1.0M
	SF01010	1T	1.0M		SF02010	2T	1.0M		SF03010	3T	1.0M		SF04010	4T	1.0M		SF05015	5T	1.5M
	SF01015	1T	1.5M		SF02015	2T	1.5M		SF03015	3T	1.5M		SF04015	4T	1.5M		SF05020	5T	2.0M
	SF01020	1T	2.0M		SF02020	2T	2.0M		SF03020	3T	2.0M		SF04020	4T	2.0M		SF05025	5T	2.5M
	SF01025	1T	2.5M		SF02025	2T	2.5M		SF03025	3T	2.5M		SF04025	4T	2.5M		SF05030	5T	3.0M
	SF01030	1T	3.0M		SF02030	2T	3.0M		SF03030	3T	3.0M		SF04030	4T	3.0M		SF05035	5T	3.5M
	SF01035	1T	3.5M		SF02035	2T	3.5M		SF03035	3T	3.5M		SF04035	4T	3.5M		SF05040	5T	4.0M
	SF01040	1T	4.0M		SF02040	2T	4.0M		SF03040	3T	4.0M		SF04040	4T	4.0M		SF05045	5T	4.5M
	SF01045	1T	4.5M		SF02045	2T	4.5M		SF03045	3T	4.5M		SF04045	4T	4.5M		SF05050	5T	5.0M
	SF01050	1T	5.0M		SF02050	2T	5.0M		SF03050	3T	5.0M		SF04050	4T	5.0M		SF05055	5T	5.5M
	SF01055	1T	5.5M		SF02055	2T	5.5M		SF03055	3T	5.5M		SF04055	4T	5.5M		SF05060	5T	6.0M
	SF01060	1T	6.0M		SF02060	2T	6.0M		SF03060	3T	6.0M		SF04060	4T	6.0M				
													SF05005	4T	0.5M				