

# ESSENTIAL HARNESS: QUICK RELEASE BUCKLES

## DESCRIPTION

Essential Harness with Quick Release Padded Buckles

Part Code: **H101QR**

## FEATURES & BENEFITS

- Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment
- High Tenacity UV stabilised webbing, enhances resistance to solvents and UV light degradation
- Retro-Reflective Thread in webbing for improved visibility in low light
- Large Dorsal D Ring for easier connection
- Closed Loop Webbing system on rear Dorsal D maintains positioning of Dorsal D in the event of a fall. Significantly reducing the risk of injury from hardware hitting the back of workers head
- Extended Belay Loops make connection of hardware easier, also maintains absolute front and centre positioning as per AS/NZS requirements
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker
- Articulated Chest Strap and shoulder adjustment points, designed for additional user comfort and female users, due to lower positioning of strap
- Quick Release Buckles. Padding under buckles
- Service Pouch on back

## APPLICATIONS

Fall Arrest, Construction, Ladder, Scaffolding, Warehouse

**EXCEEDS**



**H101QR**

# ESSENTIAL HARNESS: QUICK RELEASE BUCKLES

**EXCEEDS**



Australian  
Standard  
AS/NZS 1891.1:2007  
Lic: 21481  
SAI Global




## PRODUCT DETAILS

- AUS/NZ designed and engineered
- Sizes: S, M, L, XL, 2XL
- Quick Release padded buckles
- 10 year life span from date of manufacture



Dorsal  
D Ring



Retro Reflective Thread



Quick Release  
Buckles

**Webbing Material:** Polyester; 45mm; UV Resilient

**Buckle Material:** Corrosion resistant electrophoresis; high tensile lightweight alloy steel

**Fall Arrest Hardware** Drop Forged corrosion resistant electrophoresis; high strength alloy steel

**Thread:** Polyester; 9.81 Newtons (10kg); Extension at break 19.5%

**Stitch Pattern:** THETA Pattern combines 313 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast

**Plastic Material:** UV stabilised high density polyethylene

**Weight:** 1.1kg

**Web Tenacity:** Range: Min 28kN - Max 30kN

**Drop Forged D Rings:** Alloy Steel (standard): 40kN

**Buckle Strength:** 12 to 17kN model dependent; Laser etched or hard marked on buckle

**Padding Material:** Neoprene laminate

Reading of LINQ instruction manual prior to use is mandatory.  
Description and specification subject to change without notice.