

ESSENTIAL HARNESS: STAINLESS STEEL

DESCRIPTION

Essential Harness with Stainless Steel Hardware

Part Code: **H101SS**

FEATURES & BENEFITS

- Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment
- High Tenacity UV stabilised webbing, enhances resistance to solvents and UV light degradation
- Retro-Reflective Thread in webbing for improved visibility in low light
- Large Dorsal D Ring for easier connection
- Closed Loop Webbing system on rear Dorsal D maintains positioning of Dorsal D in the event of a fall. Significantly reducing the risk of injury from hardware hitting the back of workers head
- Extended Belay Loops make connection of hardware easier, also maintains absolute front and centre positioning as per AS/NZS requirements
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker
- Articulated Chest Strap and shoulder adjustment points, designed for additional user comfort and female users, due to lower positioning of strap
- 100% Stainless Steel Hardware for extended life in most corrosive environments
- Padding under buckles
- Service Pouch on back

APPLICATIONS

Fall Arrest, Construction, Ladder, Scaffolding, Warehouse, Corrosive Environments

EXCEEDS



H101SS

ESSENTIAL HARNESS: STAINLESS STEEL

EXCEEDS




Australian
Standard
AS/NZS 1891.1:2007
Lic: 21481
SAI Global




PRODUCT DETAILS

- AUS/NZ designed and engineered
- Sizes: S, M, L, XL, 2XL
- 2bar 3bar connector buckles
- 10 year life span from date of manufacture



**Dorsal
D Ring**



Retro Reflective Thread



**Buckle
Connectors**

Webbing Material: Polyester; 45mm; UV Resilient

Buckle Material: Corrosion resistant electrophoresis;
100% stainless steel

Fall Arrest Hardware Drop Forged corrosion resistant
electrophoresis; 100% stainless steel

Thread: Polyester; 9.81 Newtons (10kg);
Extension at break 19.5%

Stitch Pattern: THETA Pattern combines 313 stitches to exceed
28kN of strength;
AS/NZ compliant colour contrast

Plastic Material: UV stabilised high density polyethylene

Weight: 1.1kg

Web Tenacity: Range: Min 28kN - Max 30kN

Drop Forged D Rings: 100% stainless steel: 40kN

Buckle Strength: 12 to 17kN model dependent;
Laser etched or hard marked on buckle

Padding Material: Neoprene laminate

Reading of LINQ instruction manual prior to use is mandatory.
Description and specification subject to change without notice.