

DESCRIPTION

Tactician Riggers Harness

Part Code: **H201**

FEATURES & BENEFITS

- Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment
- High Tenacity UV stabilised webbing, enhances resistance to solvents and UV light degradation
- Retro-Reflective Thread in webbing for improved visibility in low light
- Rear Barr D allows easier access and better weight distribution for twin retractable fall arrest devices
- Closed Loop Webbing system on rear Dorsal Barr D maintains positioning of Dorsal D in the event of a fall. Significantly reducing the risk of injury from hardware hitting the back of workers head
- Extended Belay Loops make connection of hardware easier, also maintains absolute front and centre positioning as per AS/NZS requirements
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker
- Articulated Chest Strap and shoulder adjustment points, designed for additional user comfort and female users, due to lower positioning of strap
- Confined Space Rescue Loops
- Tangle free Triangle Back Mesh
- Padding under buckles
- Service Pouch on back

APPLICATIONS

Fall Arrest, Construction, Ladder, Scaffolding, Warehouse, Confined Space



EXCEEDS



Australian Standard
AS/NZS 1891.1:2007
Lic: 21481
SAI Global

H201

EXCEEDS




PRODUCT DETAILS

- AUS/NZ designed and engineered
- Sizes: S, M, L, XL, 2XL
- Slotted Buckles - Drop Forged
- 10 year life span from date of manufacture



Dorsal
D Ring



Retro Reflective Thread



Slotted
Buckles

- Webbing Material:** Polyester; 45mm; UV Resilient
- Buckle Material:** Corrosion resistant electrophoresis; high tensile lightweight alloy steel
- Fall Arrest Hardware** Drop Forged corrosion resistant electrophoresis; high strength alloy steel
- Thread:** Polyester; 9.81 Newtons (10kg); Extension at break 19.5%
- Stitch Pattern:** THETA Pattern combines 313 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast
- Plastic Material:** UV stabilised high density polyethylene
- Weight:** 1.4kg
- Web Tenacity:** Range: Min 28kN - Max 30kN
- Drop Forged D Rings:** Alloy Steel (standard): 40kN
- Buckle Strength:** 12 to 17kN model dependent; Laser etched or hard marked on buckle
- Padding Material:** Neoprene laminate

Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.