

DESCRIPTION

Elite Riggers Harness

Part Code: **H301**

FEATURES & BENEFITS

- Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment
- Liqui-Pel Technology for liquid protection, also easier to clean the harness
- High Tenacity UV stabilised webbing, enhances resistance to solvents and UV light degradation
- Retro-Reflective Thread in webbing for improved visibility in low light
- Rear Barr D allows easier access and better weight distribution for twin retractable fall arrest devices
- Closed Loop Webbing system on rear Dorsal Barr D maintains positioning of Dorsal D in the event of a fall. Significantly reducing the risk of injury from hardware hitting the back of workers head
- Extended Belay Loops make connection of hardware easier, also maintains absolute front and centre positioning as per AS/NZS requirements
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker
- Articulated Chest Strap and shoulder adjustment points, designed for additional user comfort and female users, due to lower positioning of strap
- Comes with Suspension Trauma Strap: One-piece Webbing with a quick connection buckle for faster deployment and connection in the event of a fall
- Air COOL Padded Shoulder Straps for increased comfort and increased air flow during long periods of use
- Padded Legs for force disperison at moment of fall impact
- Confined Space Rescue Loops
- Quick Release Buckles. Padding under buckles
- Service Pouch on back

APPLICATIONS

Fall Arrest, Construction, Ladder, Scaffolding, Warehouse, Confined Space

EXCEEDS



H301

EXCEEDS



Australian
Standard
AS/NZS 1891.1:2007
Lic: 21481
SAI Global




PRODUCT DETAILS


- AUS/NZ designed and engineered
- Sizes: S, M, L
- Quick Release padded buckles
- 10 year life span from date of manufacture



**Dorsal
Barr D Ring**



Liqui-Pel Technology



**Quick Release
Buckles**

Webbing Material: Polyester; 45mm; UV Resilient;
Liqui-pel water guard option as standard

Buckle Material: Corrosion resistant electrophoresis;
high tensile lightweight alloy steel

Fall Arrest Hardware Drop Forged corrosion resistant
electrophoresis; high strength alloy steel

Thread: Polyester; 9.81 Newtons (10kg);
Extension at break 19.5%

Stitch Pattern: THETA Pattern combines 313 stitches to exceed
28kN of strength;
AS/NZ compliant colour contrast

Plastic Material: UV stabilised high density polyethylene

Weight: 1.95kg

Web Tenacity: Range: Min 28kN - Max 30kN

Drop Forged D Rings: Alloy Steel (standard): 40kN

Buckle Strength: 12 to 17kN model dependent;
Laser etched or hard marked on buckle

Padding Material: Neoprene laminate

Reading of LINQ instruction manual prior to use is mandatory.
Description and specification subject to change without notice.