TACTICIAN RIGGERS HARNESS

PART CODE: H201

PRODUCT FEATURES >

- Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment
- High Tenacity UV stabilised webbing, enhances resistance to solvents and UV light degradation
- Retro-Reflective Thread in webbing for improved visibility in low light
- Rear Barr D allows easier access and better weight distribution for twin retractable fall arrest devices
- Closed Loop Webbing system on rear Dorsal Barr D maintains positioning of Dorsal D in the event of a fall. Significantly reducing the risk of injury from hardware hitting the back of workers head
- Extended Belay Loops make connection of hardware easier, also maintains absolute front and centre positioning as per AS/NZS requirements
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker
- Comes with Suspension Trauma Strap:
 One-piece Webbing with a quick connection
 buckle for faster deployment and connection
 in the event of a fall.
- Articulated Chest Strap and shoulder adjustment points, designed for additional user comfort and female users, due to lower positioning of strap
- Confined Space Rescue Loops
- Tangle free Triangle Back Mesh
- · Padding under buckles
- · Service Pouch on back

APPLICATIONS >

Fall Arrest, Construction, Ladder, Scaffolding, Warehouse, Confined Space

STANDARDS >









Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

AUS: 1300 546 747 NZ: 0800 546 747 INTERNATIONAL: +61 1300 546 747 WWW.LINQHS.COM

TACTICIAN RIGGERS HARNESS

PART CODE: H201

HEIGHT SAFETY

PRODUCT DETAILS >

- · AUS/NZ designed and engineered
- Sizes ranges available Small, Standard (M-L) and Maxi (XL-2XL)
- · 10 year life span from date of manufacture



DORSAL D RING



SLOTTED BUCKLES



TRAUMA POUCH



RETRO REFLECTIVE THREAD

TECHNICAL INFORMATION >

- · Webbing Material: Polyester; 45mm; UV Resilient
- Buckle Material: Corrosion resistant electrophoresis; high tensile lightweight alloy steel
- Fall Arrest Hardware: Drop Forged corrosion resistant electrophoresis; high strength alloy steel
- Thread: Polyester; 9.81 Newtons (10kg); Extension at break 19.5%
- Stitch Pattern: THETA Pattern combines 313 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast
- · Plastic Material: UV stabilised high density polyethylene
- · Weight: 1.4kg
- · Web Tenacity: Range: Min 28kN Max 30kN
- Drop Forged D Rings: Alloy Steel (standard): 40kN
- Buckle Strength: 12 to 17kN model dependent; Laser etched or hard marked on buckle
- · Padding Material: Neoprene laminate





Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

AUS: 1300 546 747 NZ: 0800 546 747 INTERNATIONAL: +61 1300 546 747 WWW.LINQHS.COM