TACTICIAN HARNESS: MULTI-PURPOSE PART CODE: H202

PRODUCT FEATURES >

- Pebble Weave Webbing design provides maximum grip for buckles, eliminating webbing slippage and the need for continual re-adjustment.
- High Tenacity UV stabilised webbing, enhances resistance to solvents and UV light degradation.
- Retro-Reflective Thread in webbing for improved visibility in low light.
- Rear Barr D allows easier access and better weight distribution for twin retractable fall arrest devices.
- Closed Loop Webbing system on rear Dorsal Barr D maintains positioning of Dorsal D in the event of a fall. Significantly reducing the risk of injury from hardware hitting the back of workers head.
- Extended Belay Loops make connection of hardware easier, also maintains absolute front and centre positioning as per AS/NZS requirements.
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker.
- Articulated Chest Strap and shoulder adjustment points, designed for additional user comfort and female users, due to lower positioning of strap.
- Comes with Suspension Trauma Strap: One-piece Webbing with a quick connection buckle for faster deployment and connection in the event of a fall.
- Confined Rescue Loops.
- Tangle free Triangle Back Mesh.
- Large Pole strap Side D's for ease of connecting Pole Strap (work positioning).
- · Adjustable Waist Belt with tool attachments.
- Padding under buckles.
- Service Pouch on back.

APPLICATIONS >

Fall Arrest, Construction, Ladder, Scaffolding, Warehouse, Confined Space, Positioning Restraint

STANDARDS >



AUS: 1300 546 747





TACTICIAN HARNESS: MULTI-PURPOSE PART CODE: H202

PRODUCT DETAILS >

- AUS/NZ designed and engineered
- Sizes ranges available Small, Standard (M-L) and Maxi (XL-2XL)
- 10 year life span from date of manufacture











SLOTTED BUCKLES

TECHNICAL INFORMATION >

- Webbing Material: Polyester; 45mm; UV Resilient
- **Buckle Material:** Corrosion resistant electrophoresis; high tensile lightweight alloy steel
- Fall Arrest Hardware: Drop Forged corrosion resistant electrophoresis; high strength alloy steel
- Thread: Polyester; 9.81 Newtons (10kg); Extension at break 19.5%
- Stitch Pattern: THETA Pattern combines 313 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast
- Plastic Material: UV stabilised high density polyethylene
- Weight: 1.4kg
- Web Tenacity: Range: Min 28kN Max 30kN
- Drop Forged D Rings: Alloy Steel (standard): 40kN
- Buckle Strength: 12 to 17kN model dependent; Laser etched or hard marked on buckle
- Padding Material: Neoprene laminate



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

