

# KERNMANTLE ROPE with THIMBLE EYE & TERMINATION

Conforms to AS 4142.3

## DESCRIPTION

Kernmantle Rope with Thimble Eye and Termination  
Part Code: **RK** + Metres Required

## FEATURES & BENEFITS

- Kernmantle rope is rope constructed with its interior core protected by a woven exterior sheath designed to optimise strength, durability, and flexibility. The core fibers provide the tensile strength of the rope, while the sheath protects the core from abrasion during use
- Pull tested to and minimum requirement: Min requirement is 29.4kN, actual 40kN+ (Have understated the test cert for prudence purposes, the test was stopped at 36kN)
- Knot test to and minimum requirement: Min requirement is 14.7kN, actual is 20kN+ (Have understated the test cert for prudence purposes, the test was stopped at 17kN)
- Rope has clear I.D trace built in
- Normal 4142.3 rope contains 80g, where as LINQ rope contains 110g. The outer casing is very tight for abrasion resistance

## PRODUCT DETAILS

- AUS/NZ designed and engineered
- 12mm kernmantle rope
- Available in 15M, 20M, 25M, 30M, 40M, 50M, 60M, 75M and 100M lengths

<b>Knot Test</b>	<14.7kN
<b>Minimum Breaking Load</b>	>35kN
<b>Outer Casing</b>	Polyester
<b>Inner/Core</b>	Polyester
<b>Weight</b>	110g
<b>Elongation Requirement</b>	Greater than 1%, less than 10% when a load equal to 10% of MBL is applied. Actual elongation when 10% of MBL is applied: 6%



**RK**

Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.