

SELF RETRACTING 2.5M WEBBING LANYARD WITH 2 x SCREW GATE KARABINERS

PART CODE: **IRW225KSKS**



**HEIGHT
SAFETY**

Engineered for extreme workplace situations, with the addition of a swivel connection point, the SRL has been developed to be durable and efficient. It extends and retracts automatically, allowing the user to operate within the recommended work area permitted by the AS/NZS Standard. The lanyard maintains tension which clears the work zone of any loose and dangerous excess webbing. In the event of a fall, a brake activates, arresting the fall and reducing the impact of the fall.

PRODUCT FEATURES >

- High impact polymer outer casing.
- Inbuilt energy absorber for enhanced shock absorption.
- Reduces impact forces to less than 6kN.

PRODUCT DETAILS >

- **Weight:** 1.35kg
- **Retractable webbing maximum length:** 2.5m
- **Mass held rating:** 136kg
- **Minimum breaking strength:** 15kN

WEBBING:

- **Material:** Polyester
- **Width:** 50mm
- **Minimum breaking strength:** 23kN

SHOCK PACK:

- **Plastic cover material:** PVC
- **Material of tear webbing:** Nylon
- **Static preload strength:** 2kN

STITCHING THREAD:

- **Material:** High tenacity polyester

VITAL TEST COMPLIANCE >

- **Static strength:** 15kN for 3 minutes
- **Dynamic performance:** Maximum breaking force does not exceed 6kN when tested with a free-falling mass of 100kg

STANDARDS >

Conforms to standard EN 360:2002. Passed the corrosion test in accordance with ISO 9227:1990 - 24 hours. Accepted under AS/NZS1891.3:2020.



Reading of LINQ instruction manual prior to use is mandatory.
Description and specification subject to change without notice.