

STANDARD ROOFERS KIT

PART CODE: **KITRSTD**



**HEIGHT
SAFETY**

PRODUCT INFORMATION >

The LINQ Standard Roofers Kit has been designed to meet the general requirements of workers who are working at heights. The kit offers exceptional value for money as opposed to buying the items individually. If your site has specific requirements, LINQ also offers a custom kit service. Customers can take advantage of the LINQ custom kit service by tailoring a kit to suit the needs of their individual work site, choosing from any LINQ harnesses, lanyards, ropes, karabiners and accessories.



WL01SNSN: Shock Absorbing Webbing Lanyard Single Hook 2X SNAP HOOK

- Batch tested to AS/NZS 1891.1: 3.8m drop using 100kg test weight, reducing forces to under 4.5kN
- An exclusive Extended Length Energy Absorber (ELEA) designed to protect a worker, of up to 150kg, tools and equipment
- Drop forged lanyard hardware for added strength in case of extreme conditions
- Contrast stitch thread colour for easy inspection and AS/NZS 1891.5 compliance



RKRG015: 15M Kernmantle Rope C/W Rope Grab & Thimble Eye

- Kernmantle rope exceeds 14.7kN
- 12mm thickness +/-
- 110gm of polyester as opposed to 65gm. This results in exceptional strength capabilities
- Rope grab as per restraint technique, in order to ensure stopping force is less than 6kN, rope grab should always be used in conjunction with a shock absorbing element



KIT INCLUDES >

HSKB710: Kit Bag

- Heavy duty waterproof duffel kit bag.
- Secures and protects parts until next use.
- Dimensions: 720mm x 320mm x 135mm



KSGA18: 2 x Screw Gate Karabiner

- Opening: 18mm
- Weight: 165gm
- Rating: 25kN
- Width: 58mm
- Length: 110mm



HSASE2515: Anchor Strap Endless

- 25mm - 1.5M
- Rated to 22kN



H101: Essential Harness

- Pebble weave webbing provides maximum grip precluding incidental buckle slippage
- Combined belay loop sub pelvic strap positioning reduces risk of throat and facial injury at moment of impact
- Retro-reflectivity built into webbing
- 150kg wearer capacity (combined weight of wearer, clothing and tools) when used in conjunction with LINQ shock absorbing lanyard
- Articulated chest and shoulder straps adjustment points designed for female wearers
- Contrast stitch thread colour for easy inspection and AS/NZS 1891.1 compliance



Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice. If in doubt please contact the LINQ helpline.

AUS: 1300 546 747

NZ: 0800 546 747

INTERNATIONAL: +61 1300 546 747

WWW.LINQHS.COM