

# SELF-RETRACTING 20M TYPE 3 LOQ-BLOQ WITH RETRIEVAL FUNCTION

PART CODE: **SRLC20R**



**HEIGHT  
SAFETY**

Engineered for extreme workplace situations, the SRL has been developed to be durable and efficient. It extends and retracts automatically, allowing the user to operate within the recommended work area permitted by the AS/NZS Standard. The lifeline maintains tension which clears the work zone of any loose and dangerous excess wire. In the event of a fall, a brake activates, arresting the fall and reducing the impact of the fall. The "Dual Mode" locking pin and handle allow for easy activation on the job, removing the hassle and frustration.

## PRODUCT FEATURES >

- High impact aluminium outer casing.
- Comes with load indicator swivelling triple action karabiner hook.
- Anchorage eye with swivel action prevents undue twisting of rope while working or in the event of a fall.
- Equipped with locking pin that enables SRL to have "Dual Mode".
- "Block Mode" allows SRL to be used as an independent fall arrestor.
- "Winch Mode" enable easy retrieval/rescue of worker.
- Full-service facility available.
- Up to five years service-free\* and then periodic servicing required.

## PRODUCT DETAILS >

- **Weight:** 18kg  $\pm$  10gm
- **Retractable wire rope maximum length:** 20m
- **Mass held rating:** 140kg
- **Material:** Galvanised steel
- **Thickness:** 4.8mm
- **Minimum breaking strength:** 12kN

## VITAL TEST COMPLIANCE >

- **Static strength:** 15kN for 3 minutes
- **Dynamic performance:** Maximum breaking force does not exceed 6kN when tested with a free-falling mass of 100kg

## STANDARDS >

Conforms to ANSI Z359.14-2021 accepted under AS/NZS 1891.3.



Reading of LINQ instruction manual prior to use is mandatory.  
Description and specification subject to change without notice.

\* subject to usage hours and work environment.

