

ESSENTIAL HARNESS: HOT WORKS

PART CODE: **H101QR-HW**



**HEIGHT
SAFETY**

PRODUCT FEATURES >

- Kevlar/Nomex webbing provides high resistance to heat and does not melt when exposed to heat whereby standard polyester will.
- Large Dorsal D Ring for easier connection.
- Closed Loop Webbing system on rear Dorsal D maintains positioning of Dorsal D in the event of a fall. Significantly reducing the risk of injury from hardware hitting the back of workers head.
- Extended Belay Loops make connection of hardware easier, also maintains absolute front and centre positioning.
- Sub Pelvic Strap integration along the line of Belay Loops, places the worker away from hardware in the event of a fall, significantly reducing the risk of injury from hardware hitting the worker.
- Unique Theta Stitch Pattern - deflects side loading and inhibits stitch popping. Contrasting stitch colour makes for easier inspection of excessive stitch loading.
- Articulated Chest Strap and shoulder adjustment points, designed for additional user comfort and female users, due to lower positioning of strap.
- Quick Release Buckles. Padding under buckles.
- Confined Space Rescue Loops.
- Service Pouch on back.

APPLICATIONS >

Fall Arrest, Welding, Construction, Confined Space, all Hot Work applications.

STANDARDS >



AS/NZS 1891.1:2020
BMP 713822
BMP 713823
Australian Standard



**Working
at Height
Association**
Reaching new levels in safety



NATA
WORLD RECOGNISED
ACCREDITATION

LINQ
TEST
LAB
FACILITY

Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 546 747
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, Highbrook,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 546 747
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

LINQHS.COM
PARAMOUNTSAFETY.COM



**HEIGHT
SAFETY**

FROM

**PARAMOUNT
SAFETY PRODUCTS**



ESSENTIAL HARNESS: HOT WORKS

PART CODE: **H101QR-HW**




**HEIGHT
SAFETY**

PRODUCT DETAILS >


- AUS/NZ designed and engineered
- Size ranges available - Small, Standard (M-L) and Maxi (XL-2XL)
- 10-year life span from date of manufacture



**DORSAL
D RING**



**QUICK
RELEASE
BUCKLES**



**FRONT FALL
ARREST
ATTACHMENT
POINTS**



**PADDING
UNDER
BUCKLES**



**CONFINED
SPACE
SPREADER
BAR
ATTACHMENT
POINTS**



**KEVLAR/NOMEX
WEBBING**



TECHNICAL INFORMATION >

- **Webbing Material:** 45mm; Kevlar/Nomex (Heraclon)
- **Buckle Material:** Corrosion resistant electrophoresis; high tensile lightweight alloy steel
- **Fall Arrest Hardware:** Drop Forged corrosion resistant electrophoresis; high tensile steel
- **Thread:** Kevlar thread
- **Stitch Pattern:** THETA Pattern combines 413 stitches to exceed 28kN of strength; AS/NZ compliant colour contrast
- **Plastic Material:** UV stabilised high-density polyethylene
- **Weight:** 1.4kg
- **Web Tenacity:** 28kN
- **Drop Forged D Rings:** Alloy Steel; 40kN
- **Buckle Strength:** 12 to 17kN. Laser etched or hard marked on buckle
- **Padding Material:** Neoprene laminate



LINQ
TEST
LAB
FACILITY

WORLD RECOGNISED
ACCREDITATION

Reading of LINQ instruction manual prior to use is mandatory. Description and specification subject to change without notice.

PARAMOUNT SAFETY PRODUCTS AUSTRALIA

12 FELLOWSHIP ROAD,
GNANGARA, WA 6077
TECH SUPPORT: 1300 546 747
CUSTOMER SERVICE: 1300 770 723
EMAIL: INFO@PARAMOUNTSAFETY.COM

PARAMOUNT SAFETY PRODUCTS NEW ZEALAND

7 SIR WOOLF FISHER DRIVE, Highbrook,
EAST TAMAKI, AUCKLAND 2013
TECH SUPPORT: 0800 546 747
CUSTOMER SERVICE: 0800 888 778
EMAIL: INFO@PARAMOUNTSAFETY.CO.NZ

LINQHS.COM
PARAMOUNTSAFETY.COM



FROM

**PARAMOUNT
SAFETY PRODUCTS**